



### Ordering information Preferred types





#### 135 RLI series

U <sub>R</sub> (V)	C <sub>R</sub> (μF)	case dimensions ∅ D x L (mm)	I <sub>R</sub> 100 kHz 105 °C (mA)	Z 100 kHz 20 °C (mΩ)	form	F (mm)	catalogue number 2222.....	smallest packing quantity
10	1000	12.5 x 16	970	120	CB	5.0	135 64102	1500
					TFA	5.0	135 34102	500
	2200	12.5 x 25	1300	73	CB	5.0	135 64222	250
					TFA	5.0	135 34222	500
16	2200	16 x 20	1400	73	CB	7.5	135 90008	250
					TFA	7.5	135 90043	250
25	470	10 x 20	860	140	CB	5.0	135 66471	500
					TFA	5.0	135 36471	800
	1000	12.5 x 25	1300	71	CB	5.0	135 66102	250
					TFA	5.0	135 36102	500
3300	16 x 35	2000	45	CB	7.5	135 66332	100	
				TFA	7.5	135 36332	100	
35	1000	12.5 x 31	1500	61	CB	5.0	135 60102	750
					TFA	7.5	135 90017	250
	1000	16 x 20	1370	71	CB	7.5	135 90017	250
					TFA	7.5	135 90044	250
2200	16 x 35	2000	44	CB	7.5	135 60222	100	
				TFA	7.5	135 60222	100	
50	100	10 x 16	640	200	CB	5.0	135 61101	500
					TFA	5.0	135 31101	800
	470	12.5 x 25	1300	68	CB	5.0	135 61471	250
					TFA	5.0	135 31471	500
	1000	16 x 31	1800	50	CB	7.5	135 61102	100
					TFA	7.5	135 31102	250
63	220	12.5 x 20	890	160	CB	5.0	135 68221	500
					TFA	5.0	135 38221	500
470	16 x 25	1400	91	CB	7.5	135 68471	250	
				TFA	7.5	135 38471	250	
100	100	12.5 x 20	890	150	CB	5.0	135 69101	500
					TFA	5.0	135 39101	500

#### 150 RMI series

**NEW**

U <sub>R</sub> (V)	C <sub>R</sub> (μF)	case dimensions ∅ D x L (mm)	I <sub>R</sub> 100 kHz 125 °C (mA)	Z 100 kHz (mΩ)	form	F (mm)	catalogue number 2222.....	smallest packing quantity
10	1000	10 x 16	950	66	CB	5.0	150 64102	500
					TFA	5.0	150 34102	800
	2200	12.5 x 20	1460	37	CB	5.0	150 64222	500
					TFA	5.0	150 34222	500
16	470	10 x 12	730	97	CB	5.0	150 65471	500
					TFA	5.0	150 35471	800
	2200	12.5 x 25	1950	29	CB	5.0	150 65222	250
					TFA	5.0	150 35222	500
25	470	10 x 16	950	66	CB	5.0	150 66471	500
					TFA	5.0	150 36471	800
	1000	12.5 x 20	1460	37	CB	5.0	150 66102	500
					TFA	5.0	150 36102	500
35	220	10 x 12	730	97	CB	5.0	150 60221	500
					TFA	5.0	150 30221	800
	470	10 x 20	1180	49	CB	5.0	150 60471	500
					TFA	5.0	150 30471	800
50	470	12.5 x 20	1100	62	CB	5.0	150 61471	500
					TFA	5.0	150 31471	500
	1000	16 x 25	1800	34	CB	7.5	150 61102	250
					TFA	7.5	150 31102	250
63	100	10 x 12	420	270	CB	5.0	150 68101	500
					TFA	5.0	150 38101	800
	470	12.5 x 25	1200	67	CB	5.0	150 68471	250
					TFA	5.0	150 38471	500



#### 136 RVI series

U <sub>R</sub> (V)	C <sub>R</sub> (μF)	case dimensions ∅ D x L (mm)	I <sub>R</sub> 100 kHz 105 °C (mA)	Z 100 kHz 20 °C (mΩ)	form	F (mm)	catalogue number 2222.....	smallest packing quantity
10	1000	10 x 20	1000	62	CB	5.0	136 64102	500
					TFA	5.0	136 34102	800
	2200	12.5 x 25	1700	34	CB	5.0	136 64222	250
					TFA	5.0	136 34222	500
16	470	10 x 16	830	84	CB	5.0	136 65471	500
					TFA	5.0	136 35471	800
	2200	16 x 20	1600	38	CB	7.5	136 65222	250
					TFA	7.5	136 35222	250
4700	16 x 35	2600	22	CB	7.5	136 65472	100	
				TFA	7.5	136 35472	100	
25	470	10 x 20	1000	62	CB	5.0	136 66471	500
					TFA	5.0	136 36471	800
	1000	12.5 x 25	1700	34	CB	5.0	136 66102	250
					TFA	5.0	136 36102	500
3300	16 x 35	2600	22	CB	7.5	136 66332	100	
				TFA	7.5	136 36332	100	
35	220	10 x 16	830	84	CB	5.0	136 60221	500
					TFA	5.0	136 30221	800
	1000	16 x 20	1700	38	CB	7.5	136 60102	250
					TFA	7.5	136 30102	250
2200	16 x 35	2600	22	CB	7.5	136 60222	100	
				TFA	7.5	136 60222	100	
50	100	10 x 12	480	200	CB	5.0	136 61101	500
					TFA	5.0	136 31101	800
	470	12.5 x 25	1500	44	CB	5.0	136 61471	250
					TFA	5.0	136 31471	500
1000	16 x 31	2200	30	CB	7.5	136 61102	100	
				TFA	7.5	136 31102	250	
63	47	10 x 12	380	300	CB	5.0	136 68479	500
					TFA	5.0	136 38479	800
	100	10 x 16	580	190	CB	5.0	136 68101	500
					TFA	5.0	136 38101	800
220	12.5 x 20	870	110	CB	5.0	136 68221	500	
				TFA	5.0	136 38221	500	
470	16 x 25	1500	55	CB	7.5	136 68471	250	
				TFA	7.5	136 38471	250	
100	47	10 x 16	450	320	CB	5.0	136 69479	500
					TFA	5.0	136 39479	800
	100	12.5 x 20	800	150	CB	5.0	136 69101	500
					TFA	5.0	136 39101	500
220	16 x 25	1300	81	CB	7.5	136 69221	250	
				TFA	7.5	136 39221	250	

#### 140 RTM series

**NEW**

U <sub>R</sub> (V)	C <sub>R</sub> (μF)	case dimensions ∅ D x L (mm)	I <sub>R</sub> 100 kHz 125 °C (mA)	Z 100 kHz (mΩ)	form	F (mm)	catalogue number 2222.....	smallest packing quantity
10	470	10 x 16	420	290	CB	5.0	140 64471	500
					TFA	5.0	140 34471	800
16	2200	16 x 25	1200	65	CB	7.5	140 65222	250
					TFA	7.5	140 35222	250
					CB	5.0	140 66221	500
25	220	10 x 16	420	290	TFA	5.0	140 36221	800
					CB	5.0	140 66471	500
35	100	10 x 12	320	350	TFA	5.0	140 36471	800
					CB	5.0	140 60101	500
50	100	10 x 16	380	350	TFA	5.0	140 30101	800
					CB	5.0	140 61101	500
	220	12.5 x 20	700	150	TFA	5.0	140 36101	800
					CB	5.0	140 61221	500
1000	16 x 31	1450	50	TFA	5.0	140 31221	500	
				CB	7.5	140 61102	100	
63	47	10 x 12	300	440	TFA	7.5	140 31102	250
					CB	5.0	140 68479	500
	470	16 x 25	1100	80	TFA	5.0	140 38479	800
					CB	7.5	140 68471	250
TFA	7.5	140 38471	250					